EDSR400H

Compact Size Four Channel Digital Video Recorder





Compact Size

Four Channel Digital Video Recorder



The EDSR400H is the industry's first full-featured digital video recorder designed specifically for use in security industry. The EDSR400H incorporates all the benefits of digital video recording, is simple to install, and operates just like a VCR. Highly effi-

cient compression technology and superior resolution of recorded images make the EDSR400H stand out from the competition as the best choice for security surveillance.

Features

- Easy-to-use control panel with common VCR and Multi plexer functions
- Shuttle/Jog dial for picture-by-picture or fast/slow viewing
- · No tapes to manage, clean or replace
- · Instant retrieval of stored video
- · On-screen setup menu and system timer
- Ethernet TCP/IP connectivity for remote viewing and controlling
- Pre-Alarm and Post-Alarm process

- Built-in M-JPEG compression/decompression with configurable quality
- · Programmed with various time-lapse speeds
- RS232 and RS485 for Remote Control
- · Real-Time Live Display for all Cameras
- Variable recording speeds up to 60/50 IPS for NTSC/PAL
- · Alarm-activated recording
- Data can be stored in CompactFlash
- · 3.5" IDE Type Hard Disks for storage with Hot-Swap tray

Advantages

NO MORE VIDEO TAPES TO CHANGE AND MANAGE

The EDSR400H brings an end to VCR tape management and maintenance problems. With digital technology, it eliminates the use of VCRs and tapes. Combining all the benefits of a time lapse VCR and Digital Multiplexer in one box, the EDSR400H provides a practical, tape-free solution.

ONE PRODUCT TO INSTALL AND MAINTAIN

With the EDSR400H, images are directly recorded onto the hard disk inside the unit. Just plug in four cameras and any other external devices and the unit automatically starts recording.

FAMILIAR MULTIPLEXER FRONT PANEL OPERATION

The EDSR400H offers familiar multiplexer and VCR style control keys. Its user-friendly, step-by-step menus simplifies the installation and operator training process.

DATA CAN BE STORED IN CompactFlash CARD

Cards inserted in the CompactFlash card slot make it easier to back up recordings and transfer images to PC.



► Wide Variety of Applications for Security Surveillance



Building and Entrance



Store and Mall



Cash Vault Operation



Bank and Office

▶ Time Lapse Mode Recording Time

NTSC

Lower	15kB	Basic	:	23kB	High	:	31kB
Low	19kB	Standard		27kB	Superior	:	35kB

Recording Speed	PICTURE QUALITY(KB)							
(IPS)	LOWER	LOW	BASIC	STANDARD	HIGH	SUPERIOR		
	15	19	23	27	31	35		
60	24.7	19.5	16.1	13.7	11.9	10.6		
30	49.4	39	32.2	27.4	23.9	21.2		
20	74.1	58.5	48.3	41.2	35.8	31.7		
15	98.8	78	64.4	54.9	47.8	41.3		
10	148.1	117	96.6	82.3	71.7	63.5		
5	296.3	233.9	193.2	164.6	143.4	127		
1	1481.5	1169.6	966.2	823	716.8	634.9		
0.5	2963	2339.2	1932.4	1646.1	1433.7	1269.8		
0.3	4938.3	3898.6	3220.6	2743.5	2389.5	2116.4		
0.2	7407.4	5848	4830.9	4115.2	3584.2	3174.6		

PAL

(Estimations based on 80 GB HDD)

Recording Speed	PICTURE QUALITY(KB)							
(IPS)	LOWER	LOW	BASIC	STANDARD	HIGH 31	SUPERIOR 35		
	15	19	23	27				
50	29.6	23.4	19.3	16.5	14.3	12.7		
25	59.3	46.8	38.6	32.9	28.7	25.4		
10	148.1	117	96.6	82.3	71.7	63.5		
5	296.3	233.9	193.2	164.6	143.4	127		
2	740.7	584.8	483.1	411.5	358.4	317.5		
1	1481.5	1169.6	966.2	823	716.8	634.9		
0.5	2963	2339.2	1932.4	1646.1	1433.7	1269.8		
0.4	3703.7	2924	2415.5	2057.6	1792.1	1587.3		
0.2	7407.4	5848	4830.9	4115.2	3584.2	3174.6		
0.1	14814.8	11695.9	9661.8	8230.5	7168.5	6349.2		

Reference: 24H=1 day, 168H=1 week, 720H=1 month, 8760H=1 year

(Estimations based on 80 GB HDD)


▶ Major Operating Controls

Back View



- 1 MAIN POWER PLUG
- (2) AUDIO IN AND OUT
- (3) MAIN MONITOR
- 4 CALL MONITOR
- (5) VIDEO IN AND OUT
- 6 ALARM IN AND OUT
- 7) LAN CONNECTOR
- 8 RS232 CONNECTOR
- (9) RS485 CONNECTOR
- 10 FAN

▶ System Connecting



Specifications

Model No:	EDSR400H (Compact Size Four Channel Digital Video Recorder)					
Video Input	4 camera inputs (BNC),1Vp-p/75ohm					
Video Output	1 BNC video out (1Vp-p/75 ohm) for Main Monitor					
	1 BNC video out (1Vp-p/75 ohm) for CALL Monitor					
	4 video out (1Vp-p/75ohm)for looping					
Video Compression	M-JPEG					
Recording Resolution	720x484 (NTSC); 720x576 (PAL)					
CompactFlash Memory	Yes, Built-in Compact Flash card slot					
Alarm Input	4 alarm inputs					
Alarm Output	1 alarm output					
Video Display	Full, PIP, Quad and 2x2 zoom for Live and Playback					
Video Loss Detection	Yes					
Ethernet	RJ45 connectors for network communications					
Event Log	Yes					
Hard Disk Storage	3.5" IDE type, Hot- swappable					
Recording Mode	Continuous, Time-lapse recording, Schedule or Event Recording					
Recording Rate	Up to 60/50 fields per Second for NTSC/PAL					
Playback Rate	Up to 60/50 fields per Second for NTSC/PAL					
Playback Search	By Date/Time or Event/Segment					
Setup	On screen display setup					
User Interface	Menu Driven					
User Input Device	Front Panel Keypad					
Timer	Built-in real time clock					
Watch Dog Timer	Yes					
RS-232	9-pin female connector					
RS485	RJ11 Connector					
Dimension	320.8mm (L) x 215mm (W) x 100mm (H)					
Operating Temperature	0°C~+40°C					
Power Consumption	60W					
Power Source	AC100~240V					

- · Design and specifications are subject to change without prior notice
- · Based on United States Federal Regulation: It's required to post warning sign if an audio devices is used in conjunction with this machine.

Ordering Information

EDSR400H/80: Four Channel Digital Video Recorder with 80GB HDD **EDSR400H/160:** Four Channel Digital Video Recorder with 160GB HDD

Distributed by



® EverFocus Electronics Corp.

Head Office:

12F, No.79 Sec. 1, Shin-Tai Wu Road, Hsi-Chi, Taipei, Taiwan Tel: 886-2-2698-2334 Fax: 886-2-2698-2380 http://www.everfocus.com.tw
E-mail: marketing@everfocus.com.tw

USA Office:

2445 Huntington Drive, San Marino, CA 91108, U.S.A. Tel: 1-626-844-8888 Fax: 1-626-844-8838 Toll Free: 1-888-383-6287 or 1-888-EV-FOCUS

http://www.everfocus.com E-mail: sales@everfocus.com

Japan Office:

1809 WBG Maribu East 18F, 2-6 Nakase, Mihama-ku, Chiba city 261-7118, Japan

Tel: 81-43-212-8188 Fax: 81-43-297-0081

http://www.everfocus.com

E-mail: salesjapan@everfocus.com

Beijing Office:

Room 609, Technology Trade Building, Shandgdi Information Industry Base, Haidian District, Beijing, China
Tel: 86-10-62971096 Fax: 86-10-62971432
http://www.everfocus.com.tw
E-mail: marketing@everfocus.com.tw

European Office:

Albert-Einstein-Strasse 1, D-46446 Emmerich, Germany Tel: 49-2822-9394-0 Fax: 49-2822-939495 http://www.everfocus.de

E-mail: info@everfocus.de