

TBM-3090 9" B/W Monitor

TBM-3120 12" B/W Monitor



▶TBM-3090



▶TBM-3120

FEATURES

- ▶12V DC output to support the camera operation
- ▶2 sets video input
- ▶More than 990 TV lines high resolution
- ▶A special push door design for protecting the rotary control
- ▶Family outlook ID design of whole series
- ▶Detachable universal power cord for 90~264V AC input
- ▶Good for large-scale systems and condition

SPECIFICATION

Model	TBM-3090 9"B/W	TBM-3120 12"B/W
Operation system	EIA 525 lines / CCIR 625 lines Auto - Switchable	
Operating frequency	EIA: 15750Hz/60Hz CCIR: 15625Hz/50Hz	
Input voltage	AC 90~264V	
Input signal	Composite video 1.0 Vp-p typical	
Input Impedance	75 Ohm	
Connections	BNC Video In, Video Out, RCA Jack: Audio In, Audio Out	
DC output (Optional)	12VDC x 1	
User control Remote control (Optional)	Front: Power on/off, Contrast, Brightness AV1/AV2 switch	
CRT	9" Diagonal	12" Diagonal
CRT dot pitch	-----	
Resolution	>900 TV lines	
Linearity	H: 10% V:10%	
Audio input (Optional)	150 mVrms Typical	
Audio amplifier (Optional)	0.5 W / 8 Ohm Typical	
Power consumption	25W	35W
Operating temperature	-10°C~50°C	
Humidity	10~90%RH	
Certification	UL, CUL, TUV, FDA, FCC, CE	
Dimension (W x H x D)	221 x 235 x 252 (mm)	380 x 300 x 302 (mm)
Weight (N. W. / G. W.)	4.6Kgs / 5.4Kgs	7.0Kgs / 8.2Kgs
Container loading (20')	720 sets	450 sets



TAIWAN REGULAR ELECTRONICS CO., LTD.

NO.115, Sec.1, Yang Tong Road, Long Tanf Hsiang, Tao Yuan Hsien, Taiwan R.O.C
 Tel : 886-3-471-9108 Fax : 886-3-471-9111,471-9112
 http : www.trc.com.tw E-mail : info@trc.com.tw