

# B/W MONITOR

**TBM-3140** 14" B/W Monitor

**TBM-3200** 20" B/W Monitor



● TBM-3140



● TBM-3200

## FEATURES

- ◆ 12V DC output to support the camera operation
- ◆ 2 sets video input
- ◆ More than 900 TV lines high resolution
- ◆ A special push door design for protecting the rotary control
- ◆ Family outlook ID design of whole series
- ◆ Detachable universal power cord for 90~264V AC input
- ◆ Good for large-scale systems and condition

# SPECIFICATION

Model	TBM-3140 14" B/W	TBM-3200 20" B/W
Operation system	EIA 525 lines / CCIR 625 lines Auto - Switchable	
Operating frequency	EIA: 15750Hz/60Hz CCIR: 15625Hz/50Hz	
Input voltage	AC 90~264V	
Input signal	Composite video 1.0 Vp-p typical	
Input Impedance	75 Ohm	
Connections	BNC x 2: Video 1 In, Video 2 In RCA Jack x 2: Audio 1 In, Audio 2 In	
DC output (Optional)	12VDC x 1	
User control	Front: Power on/off, Contrast, Brightness AV1/AV2 switch	
Remote control (Optional)		
CRT	14" Diagonal	20" Diagonal
CRT dot pitch	-	
Resolution	>900 TV lines	
Linearity	H: 10% V:10%	
Audio input (Optional)	150 mVrms Typical	
Audio amplifier (Optional)	0.5 W / 8 Ohm Typical	
Power consumption	45W	53W
Operating temperature	-10° C~50° C	
Humidity	10~90%RH	
Certification	UL, CUL, TUV, FDA, FCC, CE	
Dimension (W x H x D)	346 x 330 x 364 (mm)	460 x 420 x 384 (mm)
Weight (N. W. / G. W.)	9.2Kgs / 11.0Kgs	18.8Kgs / 21.5Kgs
Container loading (20')	320 sets	144 sets



## TAIWAN REGULAR ELECTRONICS CO., LTD.

NO.115, Sec.1, Yang Tong Road, Long Tang Hsiang, Tao Yuan Hsien, Taiwan R.O.C.

Tel : 886-3-471-9108

Fax : 886-3-471-9111,471-9112

http : //www.trcctv.com

E-mail : trcctv@ms5.hinet.net