

KVM-524RG



**KVM - 524RG
64 Image Memory**

- Intercom Function
- Easy Installation
- 4 Wired in polarity
- Door Release
- Wide view angle

KVM - 524RG Function

- Easy Installation & High Quality, 4 Wired Series
- 64 Image Memory
- 2 Monitors connection with 2 Cameras
- Intercom Function
- Easy Installation
- 4 Wired in polarity
- 4" Flat Monitor
- Wide View Angle
 - Not necessary to adjust camera view angle
- Door Release Function
 - Can be combined with door opener(DO-12/option)

KVM - 524RG Specification

| | ITEM | Specification |
|----------------|-----------------------|--|
| | Power | Built-in AC 220V or 110V, 50 or 60Hz |
| | Power consumption | Max 15W, Stand by 2.5W |
| | Assurance temperature | 0 ~ 50°C |
| | CTR tube | 4 inch Flat Tube(B/W) |
| Monitor | Communication | Duplex handset conversation |
| | Call signal sound | Electric sound(Ding-dong) |
| | Output Impedance | Picture:75, Voice:600 |
| | Wiring | 4 Wired in polarity (VCC/GND/VOICE/PICTURE) |
| | Max Wiring Distancer | ∅0.65 Single Cable/50m, 5C-2V Coaxial Cable / 100m |

| | | |
|---------------|-----------------------|--|
| | Dimension | 210(W) X 222(H) X 57(D)mm |
| | Power | DC12±1V (power from monitor) |
| | Power consumption | Max 3W |
| | Assurance temperature | - 10°C ~ 50°C |
| | Camera(Image Device) | 1/3"CCD (270,000/320,000 Pixels) |
| Camera | Scanning Frequency | Horizontal 15,625KHz or 15,732KHz / Vertical 50Hz or 60Hz |
| | Lens | F:20., f=3.0mm |
| | Minimum illumination | 0.1Lux on the object(IR LED ON) |
| | Illumination | Infra-red LED |
| | Angle of picture | Diagonal 90° |
| | Dimension | 95(W) X 127(H) X 32(D)mm |

- The product may include option or additional functions.